


- ◆ COPA is a coding schema that allows effective searches in hierarchical structures.
- ◆ It's able to perform searches using metadata that is included in the pre-existing structure.
- ◆ Elements in COPA
 - ◆ Classifications
 - ◆ A set of areas in a tree structure
 - ◆ Alphanumeric codes (COPA code)
 - ◆ Relationships between different areas
 - ◆ Either different classifications



- ◆ COPA


- ◆ Resources

- ◆ Elements are associated to areas of different classifications


- ◆ **Main goal:**

- ◆ Create virtual views over a LDAP server

Plain LDAP




COPA-based Virtual View



♦ COPA

- ♦ Goal: applications understand COPA automatically.
- ♦ New object classes
 - ♦ copaVirtualViewNav
 - ♦ Defines which virtual views are available for navigate
 - ♦ copaVirtualViewSpec
 - ♦ Configuration of a virtual view
 - ♦ Where and how are areas defined
 - ♦ Which attribute is used for making a relationship between an entry and an area
 - ♦ DN are bad guys, URN are good
 - ♦ copaArea
 - ♦ Generic object for defining an area
 - ♦ copaResource
 - ♦ Generic object for making a relationship between an entry and an area

Plain LDAP



◆ dc=univ,dc=es

◆ objectClass

- ◆ organizationalUnit
- ◆ dcObject
- ◆ copaVirtualViewNav

◆ dc

- ◆ univ


◆ ou

- ◆ univ

◆ copaDefVvNav

- ◆ dc=univVV,dc=univ,dc=es


Plain LDAP



◆ dc=univVV,dc=univ,dc=es


- ◆ **objectClass**
 - ◆ dcObject
 - ◆ copaVirtualViewSpec
- ◆ **dc**
 - ◆ univVV
- ◆ **copaName**
 - ◆ University
- ◆ **description**
 - ◆ An hierarchy of the university
- ◆ **copaPrefix**
 - ◆ urn:mace:rediris.es:virtualview:univ:20061101-1.0
- ◆ **copaCodeAttr**
 - ◆ copaCode
- ◆ **copaPrintAttr**
 - ◆ copaName

Plain LDAP



- ◆ **dc=univVV,dc=univ,dc=es**
 - ◆ **copaCodeResourceAttr**
 - ◆ **copaCode**
 - ◆ **copaClassifBase**
 - ◆ **dc=areas,dc=univ,dc=es**
 - ◆ **copaAreaObjectClassName**
 - ◆ **copaArea**

Plain LDAP



- ◆ **copaCode=a1,dc=areas,dc=univ,dc=es**
 - ◆ **objectClass**
 - ◆ copaArea
 - ◆ **copaName**
 - ◆ Faculties
 - ◆ **description**
 - ◆ List of faculties
 - ◆ **copaAreaCode**
 - ◆ a1

- ◆ COPA operations in a LDAP server (I)
 - ◆ Set the beginning of a COPA-based navigation
 - ◆ Adding the object class *copaVirtualViewNav*
 - ◆ Get a list of available virtual views
 - ◆ Which the default navigation is
 - ◆ Get a list of areas
 - ◆ DN of the used virtual view
 - ◆ Optional: COPA code of the parent area
 - ◆ Get info about an area
 - ◆ DN of the used virtual view
 - ◆ COPA code of the area

- ♦ COPA operations with a LDAP server (II)
 - ♦ Get a list of resources
 - ♦ Base DN of the search
 - ♦ DN of the used virtual view
 - ♦ COPA code of the area